

# **AO TUFFMASTER**<sup>®</sup> **UNIVERSAL HEADGEAR**

### **AOSafety® Introduces the AOTuffMaster® H24M™ Universal Aluminum Headgear.**

AOSatel

#### Features and Benefits Not Offered On Other Headgear.

This versatile headgear assembly is designed to fit AOSafety hard hats, as well as many competitors' models. The assembly is made of heat-resistant materials and is excellent for use in foundries, steel mills and other high-heat applications. The AOTuffMaster H24M can be used with cap-mounted ear muffs and provides a universal platform for AOTuffMaster face shields.





Now Fits More

Hard Hat Styles

## **AO TUFFMASTER**<sup>°</sup> IIVERSAL HEADGEAR

Universal headgear fits AOSafety and the G2000 Peltor<sup>®</sup> hardhats, as well as most hardhats by the following manufacturers: North, Protector Safety, Uvex, Jackson, Bullard, ERB, MSA and Fibre Metal.

Aluminum and durable molded materials designed for high-heat applications.

Designed to fit all AOTuffMaster faceshield windows (.040" & .080" thick)

Easy-Change<sup>™</sup> system allows for window replacement in seconds.

Two-position system locks shield up out of the field of vision when not in use and pulls down easily when needed.

Exclusive attachment feature does not interfere with capmounted earmuffs.

Meets ANSI Z87.1-2003 Standard.

^	Product Code	UPC	Description	Box Dimensions	Box Wgt.	Case Dimensions	Case Wgt.
	82520-10000	0 78371 82520 1	H24M Universal Headgear	14.57" x 9.45" x 9.45"	7.17 lbs.	19.29" x 15.35" x 20.47"	28.67 lbs.

#### **Ordering Info:**

USA Tel: 1-800-225-9038 Fax: 1-800-488-8007

Canada Tel: 1-800-387-9681 Fax: 1-800-488-8007 **Export Sales:** Tel: 1-317-692-6643 Fax: 1-317-656-5828

**Technical Info:** USA & Canada Tel: 1-800-444-4774 Fax: 1-508-764-5640

**Other Countries** Tel: 1-508-764-5721 Fax: 1-508-764-5640

© 2006 Aearo Technologies. AOSafety®, Peltor®, AOTuffMaster® Easy-Change<sup>™</sup> and H24M<sup>™</sup> are trademarks licensed to Aearo Technologies.



AEARO TECHNOLOGIES · 8001 WOODLAND DRIVE · INDIANAPOLIS, IN 46278